

10ft DNV Offshore Hardtop / Open Top

Wilbert Trading B.V.

DNV 2.7-1 / EN12079/ISO10855/BV

www.wilbert-trading.eu

TECHNICAL SPECIFICATION & ENGINEERING CHEAT SHEET

MAX GROSS WEIGHT

10,160 kg

22,400 lbs

MAX PAYLOAD

7,960 kg

17,550 lbs

TARE WEIGHT

2,200 kg

4,850 lbs (±2%)

CUBIC CAPACITY

14.94 m³

530 cu. ft.

1. TECHNICAL DATA & DIMENSIONS

PARAMETER	SPECIFICATION
ISO Type / Size	10ft x 8ft x 8ft6 (12UA Hardtop)
External Length	2,991 mm (9' 11.7")
External Width	2,438 mm (8' 0.0")
External Height	2,591 mm (8' 6.0")
Internal Length	2,830 mm (9' 3.4")
Internal Width	2,340 mm (7' 8.1")
Internal Height	2,250 mm (7' 4.6")
Certification Standard	DNV 2.7-1 / EN 12079 / ISO 10855
Lifting Set Limit	Max M.G.W. Under 10,000 kg

2. VISUAL REFERENCE (UNIT # 392103 D)



3. KEY OPERATIONAL FEATURES

- Removable Tarpaulin & Roof Header:** Flexible top loading via overhead crane for tall, heavy, or irregularly shaped offshore tools and cargo.
- Swinging Rear Door Header:** Upper door header swings open to allow unobstructed straight-in loading with forklifts or overhead slings.
- Offshore Lifting Pad Eyes:** Integrated 4-point pad eye system fully certified for DNV wire rope sling sets and shackles.
- Internal Lashing Points:** Multiple heavy-duty D-rings positioned along internal side rails for cargo security during transit.

TECHNICAL DISCLAIMER & DIMENSION RESERVATION

All dimensions, weights, capacities, and technical parameters stated in this cheat sheet are indicative and provided for preliminary planning purposes only. Manufacturing tolerances (tare ±2%) and specific client retrofits may lead to minor variations in delivered units. Wilbert Trading B.V. reserves the right to alter technical specifications without prior notice.