

10ft DNV Offshore Half Height

TECHNICAL SPECIFICATION & ENGINEERING CHEAT SHEET

Wilbert Trading B.V.
DNV 2.7-1 / EN12079/ISO10855/LR
www.wilbert-trading.eu

MAX GROSS WEIGHT
10,000 kg
22,046 lbs

MAX PAYLOAD
7,850 kg
17,306 lbs

TARE WEIGHT
2,150 kg
4,740 lbs (±2%)

INTERNAL HEIGHT
1,280 mm
4' 2.4"

1. SPECIFICATIONS & RATINGS

PARAMETER	SPECIFICATION
Container Type	10ft Half Height Open Top
External Length	2,991 mm (10' 0")
External Width	2,438 mm (8' 0")
External Height	1,600 mm (5' 3")
Internal Dimensions	2,790 × 2,240 × 1,280 mm
Certification Standard	DNV 2.7-1 / EN 12079 / ISO 10855
Classification Body	Lloyd's Register (LR)
Design Temp. Range	-20 °C to +70 °C

2. VISUAL REFERENCE (UNIT # 381523 0)



3. KEY OPERATIONAL FEATURES

- Drop-Down Side/End Gate:** Removable / swing gate design for effortless crane loading of heavy subsea pipe, tools, and machinery.
- Lifting Equipment Integration:** Certified top pad eyes engineered for DNV-compliant 4-leg wire rope lifting slings with shackles.
- Removable Tarpaulin Cover:** Fitted with heavy-duty weather resistant tarpaulin and TIR cable for open-top cargo protection.
- Internal Tie-Down Rings:** Multiple heavy-duty internal lashing points along floor line for securing high-density equipment.

TECHNICAL DISCLAIMER & DIMENSION RESERVATION

All dimensions, weights, capacities, and technical parameters stated in this cheat sheet are indicative and provided for preliminary planning purposes only. Manufacturing tolerances (tare ±2%) and specific client retrofits may lead to minor variations in delivered units. Wilbert Trading B.V. reserves the right to alter technical specifications without prior notice.